

LITHOPURE

LITHOPURE E-RIKSHAW 80Ah BATTERY DATASHEET

Applicability	Model Name	LFP80-X1
	Vehicle Type	BOV
	No. Of Wheels	3W & 4W
	Rated Voltage System(V)	48
	Motor Power (kWh)	0.85~1.2
About The Pack	Chemistry	LFP
	Capacity (AH)	80
	No. Of Cells	16
	Pack Dimensions(L X B X H)(mm)	405 X 300 X 295
	Nominal voltage (V)	51.2
	Charging Time(hrs)	4
	Maximum Power(kWh)	3.98
	Battery Management System(BMS) Installed	Yes
	Maximum Continuous Discharging current (A)	50
	Weight Of Pack(kgs)	38.2
	Power connector	Anderson Connector SB-50
	Operating voltage range (V)	42 ~ 54.8
	Life Cycles @ 25degC	2000
	Specific Energy Density(Wh/kg)	140
About The Charger	Input	220VAC @ 16A
	Charging mode	CC/CV
	Standard Charging current (A)	20
	Recommended charging voltage (V)	58.4V
	Auto Over-voltage Cutoff	Yes
	Charged Indication	Green
	Charging Indication	Red
Temperature Characteristics	Over temperature protection in discharging mode(deg C)	75
	Over temperature protection in charging mode(deg C)	65
	Maximum working temperature	-20°C to +65°C
	Storage temperature(Humidity<90% & no condensation)	-30°C to +75°C
Protections	Cell over voltage protection	YES
	Cell under voltage protection	YES
	Charging over current protection	YES
	Discharging over current protection	YES
	Output short circuit protection	YES
	Cell temperature protection in discharging mode	YES
Warranty	Cycle life @ 80 DOD%	3 Years

*Specifications maybe improvised/optimized, without prior notice for betterment of product

VIJAYSHREE AUTOCOM LTD.

Premises No. 9, 5th Phase, Industrial Area, Gamharia, Seraikela-Kharsawan, Jharkhand - 832108, India
 Email: v4u@agriideas.in | Mob: +91 7980112780